



Python®

Advanced Gooseneck

Power and Performance is the best way to describe a gun so advanced that even the competition is on edge. Taking a lesson from both the Cobra® gooseneck and the Prince® XL, the Python® adds its own unique set of features with time proven design to bring together the most advanced welding gun available.



Convenient "forward trigger" location.

"Fingertip" wire speed adjustment.

EZ-Lock® barrel can easily rotate 360° to provide the perfect angle for all jobs.

Available in both **Liquid and Air Cooled** models.

Provides hours of **high speed continuous wire feed** without welder fatigue.

For **aluminum, stainless, steel and flux cored** wires.


See the accessories section for additional gas cups, barrels and contact tips.

For improved gun performance, use with Cobra® Coolant (931-0060). Designed for all Liquid Cooled MK guns and Orbital equipment.



Rated Output determined by the gun having an Air Cooled (A/C) or Liquid Cooled (L/C) barrel.

Duty Cycle 60%



Comes Complete With

Air Cooled (A/C):

- #2 Welding power cable
- 60° Air Cooled barrel
- .060" (1.5 mm) ID Contact tip
- #10, 5/8" (15.8 mm) ID Gas Cup, A/C

Liquid Cooled (L/C):

- #6 Liquid/power cable
- 60° Liquid Cooled barrel
- .060" (1.5 mm) ID Contact tip
- #10, 5/8" (15.8 mm) ID Gas Cup, L/C

Most Popular Accessories

- Barrel insulator replacement kit (005-0696)
- 5-piece Teflon liner package (931-0137)
- Insulated drive roll kit (005-064X)
- Drive roll installation/removal tool (931-0100)
- Spiral steel conduit for steel and cored wire (621-02xx)
- Tip extender, A/C only (621-0424)

MODEL NUMBER	RATED OUTPUT	WIRE FEED SPEED	WIRE TYPE AND DIAMETER	BOXED DIMENSIONS	BOXED WEIGHT
Air Cooled	Air Cooled	800 IPM	.023" - .045" solid and hard wire (0.6 mm - 1.2 mm)	15 ft and 25 ft: 26 x 12 x 5 in (660 x 305 x 127 mm)	Air Cooled
234-815 15 ft (4.6 m)	225 Amps @ 60%				15 ft: 13.1 lb (5.9 kg)
234-825 25 ft (7.6 m)					25 ft: 19.3 lb (8.8 kg)
234-835* 35 ft (10.7 m)					35 ft: 25.5 lb (11.6 kg)
234-850 50 ft (15.2 m)					50 ft: 29.9 lb (13.6 kg)
Liquid Cooled	Liquid Cooled	800 IPM	.030" - 1/16" aluminum and cored wire (0.8 mm - 1.6 mm)	35 ft and 50 ft: 28 x 14 x 6 in (711 x 356 x 152 mm)	Liquid Cooled
235-815 15 ft (4.6 m)	450 Amps @ 60%				15 ft: 13.6 lb (6.2 kg)
235-825 25 ft (7.6 m)					25 ft: 19.7 lb (8.9 kg)
235-835* 35 ft (10.7 m)					35 ft: 25.8 lb (11.7 kg)
235-850 50 ft (15.2 m)					50 ft: 34.8 lb (15.8 kg)

GUN LEAD ASSEMBLY COMPONENTS

LENGTH	CONDUIT	GAS HOSE	CONTROL CABLE	#2 POWER CABLE (A/C)	#6 POWER CABLE (L/C)	SNAKE SKIN	LIQUID HOSE
15 ft (4.6 m)	615-0601-15	552-0242-15	005-0690	843-0630-15	843-0685-15	931-0110	552-0243-15
25 ft (7.6 m)	615-0601-25	552-0242-25	005-0691	843-0630-25	843-0685-25	931-0122	552-0243-25
35 ft (10.7 m)	615-0601-35	552-0242-35	005-0740	843-0630-35	843-0685-35	931-0132	552-0243-35
50 ft (15.2 m)	615-0601-50	552-0242-50	005-0692	843-0630-50	843-0685-50	931-0123	552-0243-50

* Call factory for availability