



Python® LX


Advanced Gooseneck

The NEW Python LX combines the robust engineering of the Python and the stylish design of the Cobra® MX. Readily distinguishable color handles. Compatible Models available in MK Green, Lincoln Red, Miller Blue and Black for Fronius Euro.

When connected with the Cobramatic wire feed cabinet and interfaced with the CobraMig® 400P Pulsed MIG power supply, you get the best push-pull wire feed equipment for welding aluminum. Completely and fully synergic, the one-knob control in the Python LX returns precise and repeatable weld settings from 15 to 50 feet away.

Rated Output determined by the gun having an Air Cooled (A/C) or Liquid Cooled (L/C) barrel.

Duty Cycle 60%



Comes Complete With

Air Cooled (A/C):

- #2 Welding power cable
- 60° Air Cooled barrel
- .060" (1.5 mm) ID Contact tip
- #10, 5/8" (15.8 mm) ID Gas Cup, A/C

Liquid Cooled (L/C):

- #6 Liquid/power cable
- 60° Liquid Cooled barrel
- .060" (1.5 mm) ID Contact tip
- #10, 5/8" (15.8 mm) ID Gas Cup, L/C

Most Popular Accessories

- Barrel insulator replacement kit (005-0696)
- 5-piece Teflon liner package (931-0137)
- Insulated drive roll kit (005-0XXXX)
- Drive roll installation/removal tool (931-0100)
- Spiral steel conduit for steel and cored wire (621-02xx)
- Tip extender, A/C only (621-0424)



Air Cooled
260-8XX

Liquid Cooled
261-8XX

Plug-in direct compatibility with MK, Lincoln, Miller or Fronius systems

Compatible with all generations of Cobramatic® cabinets

Fingertip speed control protected in handle

Mechanical gas valve integrated with trigger function (bypass for full auto control)

Uses the legendary Cobra rear trigger configuration

Patented EZ-Lock® rotatable and tapered barrel design

12 in. and 18 in. straight/curved Air and Water Cooled barrel options



Python LX
Lincoln Compatible
270-8XX (A/C)
271-8XX (L/C)



Python LX
Millermatic Compatible
272-8XX (A/C)
273-8XX (L/C)



Python LX
Fronius Compatible
274-8XX (A/C)
275-8XX (L/C)

MODEL NUMBER	RATED OUTPUT	WIRE FEED SPEED	WIRE TYPE AND DIAMETER	BOXED DIMENSIONS	BOXED WEIGHT
Air Cooled	Air Cooled	800 IPM	.023" - .045" solid and hard wire (0.6 mm - 1.2 mm)	15 ft and 25 ft: 26 x 12 x 5 in (660 x 305 x 127 mm)	Air Cooled
260-815 15 ft (4.6 m)	225 Amps @ 60%				15 ft: 13.1 lb (5.9 kg)
260-825 25 ft (7.6 m)					25 ft: 19.3 lb (8.8 kg)
260-835 35 ft (10.7 m)			.030" - 1/16" aluminum and cored wire (0.8 mm - 1.6 mm)	35 ft and 50 ft: 28 x 14 x 6 in (711 x 356 x 152 mm)	35 ft: 25.5 lb (11.6 kg)
260-850 50 ft (15.2 m)					50 ft: 29.9 lb (13.6 kg)
Liquid Cooled	Liquid Cooled				Liquid Cooled
261-815 15 ft (4.6 m)	450 Amps @ 60%				15 ft: 13.6 lb (6.2 kg)
261-825 25 ft (7.6 m)					25 ft: 19.7 lb (8.9 kg)
261-835 35 ft (10.7 m)					35 ft: 25.8 lb (11.7 kg)
261-850 50 ft (15.2 m)					50 ft: 34.8 lb (15.8 kg)

GUN LEAD ASSEMBLY COMPONENTS

LENGTH	CONDUIT	GAS HOSE	CONTROL CABLE	#2 POWER CABLE (A/C)	#6 POWER CABLE (L/C)	SNAKE SKIN	LIQUID HOSE
15 ft (4.6 m)	615-0601-15	552-0250-15	005-0690	843-0630-15	843-0685-15	931-0110	552-0251-15
25 ft (7.6 m)	615-0601-25	552-0250-25	005-0691	843-0630-25	843-0685-25	931-0122	552-0251-25
35 ft (10.7 m)	615-0601-35	552-0250-35	005-0740	843-0630-35	843-0685-35	931-0132	552-0251-35
50 ft (15.2 m)	615-0601-50	552-0250-50	005-0692	843-0630-50	843-0685-50	931-0123	552-0251-50