



# Cobra® MX

## Push-Pull Gooseneck Gun




Familiar with Cobra Gold? Cobra MX is a direct replacement with a gas valve in the gun and with all of MK Products' latest features and manufacturing techniques. This gun features our famous push-pull gooseneck design and weighs only 2 lb 5 oz. The Patented Cobra MX is ready to fit all your aluminum and hard wire welding needs.

- Optional Ultra Flex power cable offers more durability and less strain when welding.
- Plug-in direct compatibility with MK, Lincoln, Miller, Fronius, ESAB and Euro systems.
- Cobra fix mount barrel with high temp barrel insulator.
- Protected fingertip speed control in the handle.
- Uses the original Cobra rear trigger location.
- Covered wire feed mechanism.
- Covered lever wire release in the handle.
- Wire feed speed 800 IPM.
- Wire type and diameter:
  - .030" - .045" solid and hard wire (0.6 mm - 1.1 mm)
  - .030" - 1/16" aluminum and cored wire (0.8 mm - 1.6 mm)

See pgs 18-24 for gas cups, barrels and contact tips.

Duty Cycle 60%



Rated Output determined by the gun having an Air Cooled (A/C) or Water Cooled (W/C) barrel.

## Cobramatic® Compatibility

CLASSIC CUP, 1/4" TIP

| AIR COOLED     |              |
|----------------|--------------|
| LENGTH         | MODEL NUMBER |
| 15 ft (4.6 m)  | 266-815      |
| 25 ft (7.6 m)  | 266-825      |
| 35 ft (10.7 m) | 266-835      |
| 50 ft (15.2 m) | 266-850      |
| WATER COOLED   |              |
| 15 ft (4.6 m)  | 262-815      |
| 25 ft (7.6 m)  | 262-825      |
| 35 ft (10.7 m) | 262-835      |
| 50 ft (15.2 m) | 262-850      |

MAX CUP, 3/8" TIP

| AIR COOLED     |              |
|----------------|--------------|
| LENGTH         | MODEL NUMBER |
| 15 ft (4.6 m)  | 267-815      |
| 25 ft (7.6 m)  | 267-825      |
| 35 ft (10.7 m) | 267-835      |
| 50 ft (15.2 m) | 267-850      |
| WATER COOLED   |              |
| 15 ft (4.6 m)  | 263-815      |
| 25 ft (7.6 m)  | 263-825      |
| 35 ft (10.7 m) | 263-835      |
| 50 ft (15.2 m) | 263-850      |

GUN LEAD ASSEMBLY COMPONENTS

| LENGTH         | GAS HOSE    | CONTROL CABLE | POWER CABLE (A/C) | POWER CABLE (W/C) | WATER HOSE  |
|----------------|-------------|---------------|-------------------|-------------------|-------------|
| 15 ft (4.6 m)  | 552-0242-15 | 005-0690      | 843-0630-15       | 005-0387-15       | 552-0243-15 |
| 25 ft (7.6 m)  | 552-0242-25 | 005-0691      | 843-0630-25       | 005-0387-25       | 552-0243-25 |
| 35 ft (10.7 m) | 552-0242-35 | 005-0740      | 843-0630-35       | 005-0387-35       | 552-0243-35 |
| 50 ft (15.2 m) | 552-0242-50 | 005-0692      | 843-0630-50       | 005-0387-50       | 552-0243-50 |

STANDARD ON ALL COBRA MX MODELS

| LENGTH         | SNAKE SKIN |
|----------------|------------|
| 15 ft (4.6 m)  | 931-0110   |
| 25 ft (7.6 m)  | 931-0122   |
| 35 ft (10.7 m) | 931-0132   |
| 50 ft (15.2 m) | 931-0123   |

OPTIONAL LEAD ASSEMBLY COMPONENTS

| LENGTH         | ULTRA FLEX POWER CABLE* |
|----------------|-------------------------|
| 15 ft (4.6 m)  | 843-0580-15             |
| 25 ft (7.6 m)  | 843-0580-25             |
| 35 ft (10.7 m) | 843-0580-35             |
| 50 ft (15.2 m) | 843-0580-50             |

ALUMINUM WELDING ONLY (MK CONNECTION)

| LENGTH         | CONDUIT ASSEMBLY |
|----------------|------------------|
| 15 ft (4.6 m)  | 615-0601-15      |
| 25 ft (7.6 m)  | 615-0601-25      |
| 35 ft (10.7 m) | 615-0601-35      |
| 50 ft (15.2 m) | 615-0601-50      |

HARD WIRE WELDING\* ONLY

| LENGTH         | FLAT SPIRAL STEEL CONDUIT ASSEMBLY |
|----------------|------------------------------------|
| 15 ft (4.6 m)  | 615-0208                           |
| 25 ft (7.6 m)  | 615-0216                           |
| 35 ft (10.7 m) | 615-0219                           |
| 50 ft (15.2 m) | 615-0218                           |

\*Air Cooled models only

\*Steel, stainless steel and flux core steel wires

See accessories and consumables for liners and contact tips (pgs 21-24).