

## Cobra® SX Compatibility

All Cobramatic® and Cobramatic compatible guns are available in lengths of 15 ft, 25 ft, 35 ft, and 50 ft.

Lincoln Compatible guns used with Lincoln Power Feed 25M (model K2536-4) require a kit for adaptability. Call factory for details.



LINCOLN, 7 PIN COMPATIBILITY

LENGTH	MODEL NUMBER
15 ft (4.6 m)	327-815
25 ft (7.6 m)	327-825
35 ft (10.7 m)	327-835
50 ft (15.2 m)	327-850

MILLER, 14 PIN COMPATIBILITY

LENGTH	MODEL NUMBER
15 ft (4.6 m)	326-815
25 ft (7.6 m)	326-825
35 ft (10.7 m)	326-835
50 ft (15.2 m)	326-850

FRONIUS, 9 PIN COMPATIBILITY

LENGTH	MODEL NUMBER
15 ft (4.6 m)	328-815
25 ft (7.6 m)	328-825
35 ft (10.7 m)	328-835
50 ft (15.2 m)	328-850

### GUN LEAD ASSEMBLY COMPONENTS - COBRA SX COMPATIBILITY MODELS

COBRA SX COMPATIBLE MODELS

LENGTH	GAS HOSE	POWER CABLE
15 ft (4.6 m)	552-0241-15	843-0640-15
25 ft (7.6 m)	552-0241-25	843-0640-25
35 ft (10.7 m)	552-0241-35	843-0640-35
50 ft (15.2 m)	552-0241-50	843-0640-50

COBRA SX COMPATIBLE MODELS - CONTROL CABLES

LENGTH	(LINCOLN, 7 PIN)	(MILLER, 14 PIN)	(FRONIUS, 9 PIN)
15 ft (4.6 m)	005-0690	005-0380-15	005-0381-15
25 ft (7.6 m)	005-0691	005-0380-25	005-0381-25
35 ft (10.7 m)	005-0740	005-0380-35	005-0381-35
50 ft (15.2 m)	005-0692	005-0380-50	005-0381-50

### ALUMINUM WELDING ONLY (COMPATIBLE GUNS)

LENGTH	CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0620-15
25 ft (7.6 m)	615-0620-25
35 ft (10.7 m)	615-0620-35
50 ft (15.2 m)	615-0620-50

### HARD WIRE WELDING\* ONLY

LENGTH	FLAT SPIRAL STEEL CONDUIT ASSEMBLY
15 ft (4.6 m)	615-0621-15
25 ft (7.6 m)	615-0621-25
35 ft (10.7 m)	615-0621-35
50 ft (15.2 m)	615-0621-50

\*Steel, stainless steel and flux core steel wires  
See accessories and consumables for liners and contact tips (pgs 21-24).

### OPTIONAL LEAD ASSEMBLY COMPONENTS

LENGTH	ULTRA FLEX POWER CABLE*
15 ft (4.6 m)	843-0715-15
25 ft (7.6 m)	843-0715-25
35 ft (10.7 m)	843-0715-35
50 ft (15.2 m)	843-0715-50

\*Air Cooled models only